Honeywell Home

Y87RF Single Zone Thermostat User Guide



Setting your room temperature

Your current room temperature is shown in the display. To set the temperature you want, just turn the dial right to increase and left to decrease. Each 'click' as the dial turns represents a 0.5° change.



After five seconds the current room temperature will be displayed once again. The thermostat will then try to maintain your set temperature as accurately as possible.

You can check your set temperature by turning the dial one 'click' to the left or right. The set temperature will flash up for a few seconds, before returning to display the room temperature again.



Night-time temperature reduction

Overnight, or if you are out, it is best to set the thermostat to a lower temperature, as it will save you energy. In general a reduction of 5°C is recommended, but this will depend on your heating system and the amount of insulation in your home.

Replacing the batteries

Your batteries should be replaced

when the symbol is displayed. To do this, separate the thermostat from the wiring plate and insert 2

new AA alkaline batteries in place

of the empty ones. Then reattach

the thermostat to the wiring plate.

Getting to know your display

Set Temperature Indicator

Means the figure on the screen is your set temperature, rather than your current room temerature.

Heating on

Means there is a requirement for some heating, so your boiler should either be on or cycling on/off.



Boiler Relay Connection

Means your thermostat is successfully connected to your Boiler Relay.



Internet Gateway Connection (optional) Means your thermostat is successfully connected to your Internet Gateway.

For support: Resideo 200 Berkshire Place Winnersh Triangle, Berkshire RG41.5R Phone: 0300 130 1299



www.resideo.com Country of origin : UK

© 2020 Resideo Technologies, Inc. All rights reserved. The Honevwell Home trademark is used under license from Honevwell International Inc. This product is manufactured by Resideo Technologies, Inc. and its affiliates.

50094158-006 B

Printed in EU.

Binding your thermostat to a RFG100 Internet Gateway

If you want to be able to operate your Single Zone Thermostat remotely or add scheduling then you will need to use the RFG100 Internet Gateway (sold separately) and bind the thermostat to it.

To do this, please follow the full installation instructions in the RFG100 box, and at the relevant binding stage follow these steps to connect your thermostat:

1. Touch and hold the right-hand touch zone for about 10 seconds to activate the binding screen.



2. Briefly touch the right-hand touch zone once again to send the binding signal. The •)) and n symbols will flash until binding is successful.




3. With good reception, the green •)) LED on the Gateway Honeywell Home will then light up to confirm te de de successful binding. 111111

Note: if you have tried to bind but have persistent problems doing so, please visit the URL below for assistance:

ensupport.getconnected.honeywellhome.com/

4. After binding, the strength of the signal between the devices will appear on the thermostat for a few seconds, 1 equals the lowest strength and 5 the highest.







Troubleshooting



If you see this battery icon then you need to replace the batteries right away. See overleaf.



. -

HOME

20.0°

No power to the thermostat

If the thermostat screen is blank after initial installation. then check the protective tab has been removed from the batteries. Otherwise, try replacing the batteries.

RF communication error

If these icons are flashing, then there may be an issue with the signal from the Boiler Relay. First check there is mains power to the Boiler Relay. If this does not resolve the problem, consult your installer.

Defective thermostat

•))][

If this icon is displayed then the thermostat is no longer functioning and will need to be replaced.