

Data Sheet Series 3 DC313NHGBS Wireless portable and plug-in doorbell with volume control and push button – White



Simple, reliable and hassle-free, the Honeywell Home DC313NHGBS home and garden kit comes with adjustable volume to suit your mood, and a LED strobe for added visual alerts. Place the plug-in doorbell inside your home and take the portable doorbell with you into the garden, so you'll always know when someone's at the door.



Pack Contents:

1 x Wireless Portable Doorbell, 1 x Wireless Plug-in Doorbell, 1 x Wireless Push Button, 1 x CR2032 (3V) Battery, 1 x Quick Start Guide, 1 x Safety & Guarantee, 1 x Declaration of Conformity,

Key Features and Benefits:

Home and Garden Kit Never miss a visitor again with this flexible home and garden kit. Place the plug-in doorbell inside your home and take the portable doorbell with you into the garden, so you'll always know when someone's at the door.

Never miss a visitor or delivery Take your portable doorbell anywhere around your home and garden, with Honeywell ActivLink™ technology providing a reliable wireless range of up to 150m, while the maximum volume of 84dB can be heard up to 80m away.

Disturbance Free - Easily adjust the volume to suit your family and mood, or when you simply want some quiet time.

Visual Alerts - The LED Strobe provides a discreet but effective visual alert which complements your chosen melody in loud environments, or helps to alert you when the doorbell can't be heard.

Revolutionary design - Compact and beautifully designed in a harmonising palette of white and grey, our doorbells are designed with your home in mind.

Peace of mind - Peace of mind for visitors, thanks to a LED confidence light on the push button, and peace of mind for you, thanks to the Secret Knock function which plays a different melody, so you know if it's a family member or friend at the door. For total peace of mind, let Honeywell ActivLink™ interconnect your doorbell with Honeywell security accessories and Home Alarm Kits to build your own bespoke home alert and alarm system.

Reliability and Quality - Honeywell ActivLink®, using the 868MHz frequency, is our innovative wireless protocol which delivers greater range capability, extended battery life of up to 2 years, and improved connection reliability, all supported by our 2 year product quality guarantee.

Specification:

Wireless Portable Doorbell

Colour	White
Wall mounted	Optional
Frequency / Transmission Power / Wireless Range*	868MHz / 150m
Audible Range (Volume)	80m (84dB)
Melodies	6
Sound	Volume Control / Internal Siren
Alarm Time (minutes)	2 (Internal Siren Mode)
Visual Alerts	LED Indicator / LED Strobe
Power	Battery: 4 x LR6 (AA) 1.5V - (not included)
Battery Life (Years)	2
Battery Features	Low Battery Indicator / Easy Open Battery Compartment
Maximum Device Capacity	4 x Wireless Push Button/Wireless Motion Sensor/Wireless Door and Window Sensor
Factory Reset	Yes
Operating Temperature/Storage Temperature	0°C to +40°C/-20°C to +60°C
Dimensions (mm) / Weight (g)	110 (h) x 70 (w) x 42.5 (d) / 169 (g)
Fixings	Brackets / Rawl Plugs / Screws

Wireless Plug-in Doorbell

Colour	White
Wall mounted	No
Frequency / Transmission Power / Wireless Range*	868MHz / 150m
Audible Range (Volume)	80m (84dB)
Melodies	6
Sound	Volume Control / Internal Siren
Alarm Time (minutes)	2 (Internal Siren Mode)
Visual Alerts	LED Indicator / LED Strobe
Power	Mains Power: 100-240V 50-60Hz 300mA
Maximum Device Capacity	4 x Wireless Push Button/Wireless Motion Sensor/Wireless Door and Window Sensor
Factory Reset	Yes
Operating Temperature/Storage Temperature	0°C to +40°C/-20°C to +60°C
Dimensions (mm) / Weight (g)	110 (h) x 70 (w) x 64 (d) / 160 (g)

Wireless Push Button

Colour	White
Wall mounted	Optional
Screwless mounting option (Sticky pads)	Yes
Frequency / Transmission Power / Wireless Range*	868MHz / 200m
Visual Alerts	Confidence Light
Power	Battery: 1 x CR2032 (3V) - (included)
Battery Life (Years)	2
Battery Features	Low Battery Indicator / Easy Open Battery Compartment
Push Button Design	Portrait
Push Name Plate	No
IP Rating	IP55
Operating Temperature/Storage Temperature	-20°C to +50°C/-20°C to +60°C
Dimensions (mm) / Weight (g)	30 (h) x 70 (w) x 16 (d) / 23.5 (g)
Fixings	Brackets / Rawl Plugs / Screws / Sticky Pads

Pack

EAN Code	5004100965431
Pack Dimensions (mm) / Weight (g)	216 (h) x 315 (w) x 88 (d) / 660 (g)
Standard Pack Quantity	4

* Measured in open field conditions, walls, ceilings and metal structures will reduce the maximum range.