



V2881, V2882



	2-100°C (36-212°F) Max. 10bar (145psi)
--	---



V2881DSL15A V2882DSL15A 	V2881LSL15A V2882LSL15A 	V2881RSL15A V2882RSL15A
--------------------------------	--------------------------------	--------------------------------



A

B

C

D

E

F

n=1 - 8
⇒ Tab. 1

Tab. 1

n	1	2	3	4	5	6	7	8
Q _{nom} , 2K p-band [kg/h]	-	20	100	200	300	300	300	300
kvs [m³/h]	-	0.06	0.32	0.65	1.2	1.5	1.7	1.9



A

B



	FEM24C12 FEM24C14 FEM24C15 FEM24C16		VA2201D012 VA2201E015 VA2201D014 VA2201E016 VA2201D015 VA2201E018 VA2201D016 VA2201E020 VA2201D018 VA2201D020 VA2201E012 VA2201E014
	FEM24P14X2 FEM24P16X1.5 FEM24P16X2 FEM24P18X2		
	FEM24M14X2 FEM24M16X2 FEM24M18X2 FEM24M20X2		T4021 T4221
	VA2200C001 VA2200C002		

For more information
homecomfort.resideo.com/europe



Ademco 1 GmbH
Hardhofweg 40
74821 MOSBACH
GERMANY
Phone: +49 6261 810
Fax: +49 6261 81309

Manufactured for and on behalf of the
Pittway Sàrl, La Pièce 4, 1180 Rolle, Switzerland
by its Authorised Representative Ademco 1 GmbH
MU2H-2110GE25 R1120
Subject to change
© 2020 Pittway Sàrl. All rights reserved.
This document contains proprietary information of
Pittway Sàrl and its affiliated companies and is
protected by copyright and other international
laws. Reproduction or improper use without specific
written authorisation of Pittway Sàrl is strictly
forbidden. The Honeywell Home trademark is used
under license from Honeywell International Inc.