



Honeywell Home Product Technical Data

Wireless Security

HS922GPRS - Smart Wireless Home Alarm Kit with GPRS



KEY FEATURES AND BENEFITS

- Our unique patented bi-directional secure 868 MHz Wireless Technology - longer range (1000m) and improved battery performance.
- Transmission using GPRS with built-in antenna.
- Standard SIM Card with roaming services.
- Ethernet port for IP connection.
- Up to 32 peripherals per installation.
- Leave your home with complete peace of mind. The APP allows you to monitor your home from a tablet or smartphone to ensure your family is safe
- Total Connect Comfort International mobile Apps enable visual verification feature which allows you to see what is happening if an alarm is activated. The home owner is notified by SMS or email and can distinguish whether an intrusion has occurred or if it is a false alarm.
- Standard SIM Card with 2 years connection period.
- Stand-by 24hrs back up in case of mains loss.
- Total Connect Comfort' iOS and Android app available in App Store and Google Play to download. Apps support all security related functions
- Web portal URL to support registration and setup: <https://international.mytotalconnectcomfort.com>

KIT CONTENTS

- 1 x Wireless Hub with GPRS
- 1 x Wireless Pet-immune Motion Sensor (PIR)
- 1 x Wireless door window sensor
- 1 x Wireless Contactless Tag Reader with built-in Siren

- 2 x Contactless tags
- 1 x SIM card
- 1 x Ethernet / LAN cable
- 1 x Universal Power Adaptor with EU and UK plug
- All required batteries
- All fixings supplied
- 1 x Quick start installation guide
- 1 x SMS activation code card
- 1 x Safety and guarantee guide
- 1 x Declaration of conformity



INSTALLATION

- Internal use only.

PRODUCT SPECIFICATION

Languages covered –
GB, DE, FR, ES, PT, IT, NL = English, German, French, Spanish, Portuguese, Italian, Dutch

- Frequency - 868MHz
- Wireless Range : 1000m (open field)
- Operating Temperature: -10°C to +55°C

| | |
|--|--|
|  | <p>Wireless Hub with GPRS – Ref: SUE8EU-STD-EG</p> <ul style="list-style-type: none"> • Comes with free e-mail notification services • Up to 32 peripherals per installation • Ethernet port for IP connection • Transmission using GPRS** with built-in antenna • Standard SIM Card with 2 years connection services • Supervision • LED System information reports • Power supply 230V~ to DC 6.5V/2A (4 x AA rechargeable batteries (supplied not fitted) • Stand-by 24h (in case of mains loss) • Low Battery Signaling • Dimensions 190 x 123 x 35 mm |
|  | <p>Wireless Pet-immune Motion Sensor (PIR) Ref : IRPI8EZ</p> <ul style="list-style-type: none"> • Pet immune up to 36kg • 10 x 12m detection range • 1 x CR123A battery with approx. 4 years life. Supplied fitted with battery isolation tab • Dimensions 112 x 60 x 40 mm |



Honeywell Home Product Technical Data Wireless Security

| | |
|---|--|
|  | <p>Wireless door window sensor Ref : DO8EZ</p> <ul style="list-style-type: none"> • 1 x CR123A with approx. 5 years life. Supplied fitted with battery isolation tab • Dimensions 102 x 22 x 23 mm |
|  | <p>Wireless Contactless Tag Reader Ref. : SPR-S8EZ</p> <ul style="list-style-type: none"> • Up to 10 users • Two buttons • Built-in siren 78dBA @1m • Four LEDs for status • 3 x CR123A with approx. 4 years life. Supplied fitted with battery isolation tab • Dimensions 110 x 110 x 30 mm |
|  | <p>Contactless tags</p> <ul style="list-style-type: none"> • 2 black • Dimensions 47 x 30 x 3 mm |

PACKAGING DATA

SINGLE PRODUCT

EAN code: 5004100969415

Weight: approx. 2400g

Pack dimension: 160 x 320 x 160mm

STANDARD PACK

Quantity: 4